

hisunmotors.com







STRIKE 900 New for 2017! 924cc V-Twin EFI Engine 4WD Width 61" L H N R Gears CVTech Trailbloc IBC CVT



#### STRIKE 250

229cc Single Cylinder EFI Engine 2WD Width 49.6" L H N R Gears



#### STRIKE 550 New for 2017! 546cc Single Cylinder EFI Engine 4WD Width 53.5" L H N R Gears



## **STRIKE 1000**

976cc V-Twin EFI Engine 4WD with EPS Width 69" L H N R Gears CVTech Trailbloc IBC CVT



STRIKE 1000 CREW 976cc V-Twin EFI Engine 4WD with EPS Width 69" L H N R Gears CVTech Trailbloc IBC CVT

	STRIKE 250	STRIKE 550	STRIKE 900	STRIKE 1000	STRIKE 1000 CREW
Engine Size	229cc	546cc	924cc	976cc	976cc
2WD/4WD	2WD	4WD	4WD	4WD	4WD
Tire Size	22"	26"	26"	27"	27"
Locking Differential		•	•	•	•
Nitrogen Shocks			•	<b>©</b>	•

See our accessory catalog for additional Strike Series accessories. 3







#### SECTOR 550

546cc Single Cylinder EFI Engine 4WD Width 62" L H N R Gears



#### SECTOR 250

229cc Single Cylinder EFI Engine 2WD Width 49" L H N R Gears



#### **SECTOR 750**

735cc Single Cylinder EFI Engine 4WD Width 62" L H N R Gears



#### SECTOR 450

454cc Single Cylinder EFI Engine 4WD Width 62" L H N R Gears



#### **SECTOR 1000**

976cc V-Twin EFI Engine 4WD with EPS Width 67" L H N R Gears CVTech Trailbloc IBC CVT

	SECTOR 250	SECTOR 450	SECTOR 550	SECTOR 750	SECTOR 1000
Engine Size	229cc	454cc	546cc	735cc	976cc
2WD/4WD	2WD	4WD	4WD	4WD	4WD
Tire Size	22"	26"	26"	26"	27"
Locking Differential		•	•	•	•
Nitrogen Shocks		<b>©</b>	<b>©</b>	<b>©</b>	•

See our accessory catalog for additional Sector Utility Series accessories. 5





#### **SECTOR 750 CREW**

New for 2017!

735cc Single Cylinder EFI Engine 4WD with EPS Width 62" L H N R Gears



#### **SECTOR 1000 CREW SECTOR 750 CREW** 976cc **Engine Size** 735cc 2WD/4WD 4WD 4WD Tire Size 26" 27" **Locking Differential Nitrogen Shocks**



### 976cc V-Twin EFI Engine

**SECTOR 1000 CREW** 

4WD with EPS Width 67" L H N R Gears CVTech Trailbloc IBC CVT

**CARGO AND CREW** 

Transport all of your crew and cargo with cargo bed capacities from 500 lbs (Sector 750) to 1000 lbs (Sector1000). In-line bench seating provides more than enough room for 4-adults.

See our accessory catalog for additional Sector Utility Series accessories. 7





#### **DISCOVER™ DRY CELL BATTERY TECHNOLOGY**



- + LONGER RUN TIME
- \* MAINTENANCE FREE
- \* SUSTAINABLE DESIGN
- \* LONGER BATTERY LIFE

	SECTOR E1
Battery	48 Volt - 38 HP
2WD/4WD	4WD
Tire Size	26"
ocking Differential	0
Nitrogen Shocks	<b>Ø</b>

#### **BUILT WITH NORTH AMERICAN DRIVE TRAIN**

KINETEK™ MOTOR +

DELTA Q™ CHARGER +

SEVCON™ CONTROLLERS \*

DISCOVER™ BATTERY +





### STANDARD ACCESSORIES

Digital Display, LED Lighting

250 - 400 ATVs

Front and Rear Cargo Racks 2500 lb Winch





#### **AXIS 110**

108cc Single Cylinder EFI Engine Width 41" F N R Gears



#### **FORGE 250**

New for 2017! 229cc Single Cylinder EFI Engine 2WD Width 42" F N R Gears



#### FORGE 110

108cc Single Cylinder EFI Engine Width 41" F N R Gears



#### FORGE 400

New for 2017! 393cc Single Cylinder EFI Engine Width 42" F N R Gears



	AXIS IIU	FORGE 110	FORGE 230	FORGE 400
Engine Size	108cc	108cc	229cc	393cc
2WD/4WD	2WD	2WD	2WD	4WD
Tire Size	21"	21"	25"	25"
Suspension F/R	Independent / Swing Arm	Independent / Swing Arm	Independent / Swing Arm	Independent / Swing Ai

An electronic fuel injected engine is at the heart of every HISUN Forge ATV. From youth models to the new Forge 400 Standard Winch 2500 lb you'll find standard features only found on a HISUN.

FORGEATV

**ATVs** 

2500 lb







### **TACTIC 450**

454cc Single Cylinder EFI Engine 4WD Width 50.3" L H N R Gears



#### **TACTIC 750**

735cc Single Cylinder EFI Engine 4WD Width 50.3" L H N R Gears



#### TACTIC 550

546cc Single Cylinder EFI Engine 4WD Width 50.3" L H N R Gears



#### **TACTIC 1000**

976cc Single Cylinder EFI Engine Width 51.6" 4WD with EPS L H N R Gears CVTech Trailbloc IBC CVT

	TACTIC 450	TACTIC 550	TACTIC 750	TACTIC 1000
Engine Size	454cc	546cc	735cc	976cc
2WD/4WD	4WD	4WD	4WD	4WD
Tire Size	26"	26"	26"	27"
Locking Differential	•	<b>©</b>	•	•
Nitrogen Shocks	•	•	•	•

See page 19 for important safety information for all HISUN ATVs. 13

### STRIKE SPORT SERIES

STRIKE 250 STRIKE 550 STRIKE 900 STRIKE 1000 STRIKE 1000 CREW











Type  Displacement Bore & Stroke Compression Ratio	4-Stroke - OHV Single Cylinder 229 cc 65.5 x 68 9.7 : 1	4-Stroke - OHV Single Cylinder 546 cc 91 x 84 9.6 : 1	4-Stroke - OHV V-Twin Cylinders 924 cc 91 x 71 10.5 : 1	4-Stroke - OHV V-Twin Cylinders 976 cc 91 x 75 11 : 1	4-Stroke - OHV V-Twin Cylinders 976 cc 91 x 75 11 : 1
Fuel System  Cooling Ignition System	Delphi EFI Liquid Electronic	Delphi EFI Liquid Electronic	Delphi EFI Liquid Electronic	Delphi EFI Liquid Electronic	Delphi EFI Liquid Electronic
Drive Train	2.000.010		2.000.00		2.55555
Transmission	Automatic CVT	Automatic CVTech	Automatic CVTech Trailbloc IBC	Automatic CVTech Trailbloc IBC	Automatic CVTech Trailbloc IBC
Drive System	2WD L H N R	4WD with Locking Differential L H N R	4WD with Locking Differential L H N R	4WD with Locking Differential L H N R	4WD with Locking Differential L H N R
Final Drive	Chain Drive	Shaft Drive	Shaft Drive	Shaft Drive	Shaft Drive
Chassis / Suspension / Brakes					
Suspension Front	Independent Dual A-arm	Independent Dual A-arm	Indep. Dual A-Arm / Nitrogen Assist	Indep. Dual A-Arm / Nitrogen Assist	Indep. Dual A-Arm / Nitrogen Assist
Suspension Rear	Swing Arm	Independent Dual A-arm	Indep. Dual A-Arm / Nitrogen Assist	IIndep. Dual A-Arm / Nitrogen Assist	Indep. Dual A-Arm / Nitrogen Assist
Brakes Front	Dual Ventilated Hydraulic Disc	Dual Ventilated Hydraulic Disc	Dual Ventilated Hydraulic Disc	Dual Ventilated Hydraulic Disc	Dual Ventilated Hydraulic Disc
Brakes Rear	Single Ventilated Hydraulic Disc	Dual Ventilated Hydraulic Disc	Dual Ventilated Hydraulic Disc	Dual Ventilated Hydraulic Disc	Dual Ventilated Hydraulic Disc
Tires Front Tires Rear	AT 22 x 7-10 Radial AT 22 x 10-10 Radial	AT 26 x 9-14 Radial AT 26 x 11-14 Radial	AT 26 x 9-14 Radial AT 26 x 11-14 Radial	AT 27 x 9-14 Radial AT 27 x 11-14 Radial	AT 27 x 9-14 Radial AT 27 x 11-14 Radial
Dimensions					
Length x Width x Height Wheel Base Fuel Capacity Vehicle Weight Cargo Bed Capacity Towing Capacity Ground Clearance	88.9" x 49.6" x 59" 68.2" 3.5 Gallons 688 lbs. 50 lbs. N/A 8" Front / 5.8" Rear	106" x 53.5" x 72.5" 76" 7 Gallons 1244 lbs. 350 lbs. 1200 lbs. 12"	106" x 61" x 72.5" 76" 7 Gallons 1286 lbs. 350 lbs. 1200 lbs. 12"	113.4" x 69.3" x 74.8" 85" 7.3 Gallons 1388 lbs. 350 lbs. 1200 lbs. 13"	138.2" × 69.3" × 76.77" 103.5" 7.3 Gallons 1631 lbs. 350 lbs. 1200 lbs. 13"
Other Instrumentation / Special Features	Digital Display, 2500 lb Winch, Roof, Windshield, Aluminum Rims, Turn Signals, Doors, Horn	Digital Display, 3500 lb Winch, Roof, Windshield, Aluminum Rims, Turn Signals, Horn	Digital Display, CVTech Trailbloc IBC Clutch, 3500 lb Winch, Roof, Windshield, Aluminum Rims, Turn Signals, Horn	Digital-Analog Display, CVTech Trailbloc IBC Clutch, 3500 lb Winch, Aluminum Rims, LED Lighting, Roof, Windshield, Gas Shocks, Horn, Electronic Power Steering, Turn Signals	Digital-Analog Display, CVTech Trailbloc IBC Clutch, 4500 lb Winch, Aluminum Rims, LED Lighting, Roof, Windshield, Gas Shocks, Horn, Electronic Power Steering, Turn Signals
Compliance	EPA / CARB	EPA / CARB	EPA / CARB	EPA / CARB	EPA / CARB
Color Options	Black, Red, White	Black, Red, White	Black, Red, White	Black, Red, White	Black, Red, White
Warranty	2 Year Limited	2 Year Limited	2 Year Limited	2 Year Limited	2 Year Limited

## SECTOR UTILITY SERIES

SECTOR 250

SECTOR 450

SECTOR 550

SECTOR 750

SECTOR 1000

4-Stroke - OHV
Single Ollinder
Single Ollinder
Single Ollinder
Single Ollinder

Camo, Black, Red

2 Year Limited

Camo, Black, Red

2 Year Limited

Camo, Black, Red

2 Year Limited

Engine					
Type	4-Stroke - OHV Single Cylinder	4-Stroke - OHV Single Cylinder	4-Stroke - OHV Single Cylinder	4-Stroke - OHV Single Cylinder	4-Stroke - OHV V-Twin Cylinders
Displacement	229 cc	454 cc	546 cc	735 cc	976 cc
Bore & Stroke	65.5 x 68	83 x 84	91 x 84	102 × 90	91 x 75
Compression Ratio	9.7 : 1	9.4 : 1	9.6 : 1	9.7 : 1	11:1
Fuel System	Delphi EFI	Delphi EFI	Delphi EFI	Delphi EFI	Delphi EFI
Cooling	Liquid	Liquid	Liquid	Liquid	Liquid
Ignition System	Electronic	Electronic	Electronic	Electronic	Electronic
Drive Train					
Transmission	Automatic CVT	Automatic CVT	Automatic CVT	Automatic CVT	Automatic CVTech Trailbloc IBC
Drive System	2WD	4WD with Locking Differential	4WD with Locking Differential	4WD with Locking Differential	4WD with Locking
	LHNR	LHNR	LHNR	LHNR	Front / Rear Differential L H N R
Final Drive	Chain Drive	Shaft Drive	Shaft Drive	Shaft Drive	Shaft Drive
Chassis / Suspension / Brakes					
Suspension Front	Independent Dual A-arm	Indep. Dual A-Arm / Nitrogen Assist	Indep. Dual A-Arm / Nitrogen Assist	Indep. Dual A-Arm / Nitrogen Assist	Indep. Dual A-Arm / Nitrogen Assist
Suspension Rear	Swing Arm	Indep. Dual A-Arm / Nitrogen Assist	Indep. Dual A-Arm / Nitrogen Assist	Indep. Dual A-Arm / Nitrogen Assist	Indep. Dual A-Arm / Nitrogen Assist
Brakes Front	Dual Ventilated Hydraulic Disc	Dual Ventilated Hydraulic Disc	Dual Ventilated Hydraulic Disc	Dual Ventilated Hydraulic Disc	Dual Ventilated Hydraulic Disc
Brakes Rear	Single Ventilated Hydraulic Disc	Dual Ventilated Hydraulic Disc	Dual Ventilated Hydraulic Disc	Dual Ventilated Hydraulic Disc	Dual Ventilated Hydraulic Disc
Tires Front	AT 22 x 7-10 Radial	AT 26 x 9-12 Radial	AT 26 x 9-14 Radial	AT 26 x 9-14 Radial	AT 27 x 9-14 Radial
Tires Rear	AT 22 x 10-10 Radial	AT 26 x 10-12 Radial	AT 26 x 11-14 Radial	AT 26 x 11-14 Radial	AT 27 x 11-14 Radial
Dimensions					
Length x Width x Height	94" x 48.8" x 66"	110" × 61.75" × 73"	117.2" × 61.75" × 76.75"	117.2" × 61.75" × 76.75"	122.5" × 66.5" × 77.75"
Wheel Base Fuel Capacity	68.2" 3.5 Gallons	72.5" 7.3 Gallons	76.75" 7.3 Gallons	76.75" 7.3 Gallons	84.5" 7.3 Gallons
Vehicle Weight	725 lbs.	1300 lbs.	1363 lbs.	7.3 Galloris 1363 lbs.	1697 lbs.
Cargo Bed Capacity	250 lbs.	350 lbs.	500 lbs.	500 lbs.	1000 lbs.
Towing Capacity	N/A	1200 lbs.	1200 lbs.	1200 lbs.	1200 lbs.
Ground Clearance	8" Front	9.7"	12"	12"	13"
Other					
Instrumentation / Special Features	Digital Display, 2500 lb Winch,	Digital-Analog Display,	Digital-Analog Display,	Digital-Analog Display,	Digital-Analog Display,
	Roof, Windshield, Turn Signals, Aluminum Rims	3500 lb Winch, Roof, Windshield, Aluminum Rims,	3500 lb Winch, Roof, Windshield, Aluminum Rims, Doors,	3500 lb Winch, Roof, Windshield, Aluminum Rims, Doors,	4500 lb Winch, Roof, Windshield, Aluminum Rims, Adjustable Gas Shock
	Aluminum Rims	Adjustable Gas Shocks	Adjustable Gas Shocks.	Adjustable Gas Shocks.	Electronic Power Steering, CVTech
		/ lajastable das allocks	Optional Electronic Power Steering	Optional Electronic Power Steering	Trailbloc IBC Clutch,
Compliance	EPA / CARB	EPA / CARB	EPA / CARB	EPA / CARB	Power Cargo Dump
Calar Online	Course Black Book	Carra Black Bad	Corres Blanks Bank	Carra Blad Bad	EPA / CARB

Camo, Black, Red

2 Year Limited

4

Color Options

Warranty

Camo, Black, Red

2 Year Limited

### SECTOR ET

SECTOR E1



SECTOR 750 CREV

SECTOR 1000 CREW





AC-Induction
48
38
220
1
Discover™ Dry Cell Technology
2080 Amp/Hours
6-8 Hours
On-Board Charger

Drive	
Drive Mode	Low, Medium, High
Max Speed	25 Miles
Range	>45 Miles*
4x4 Mode	Selectable

\* Range estimates assume a full charged battery pack. Actual range results are highly dependent on driving style, drive mode selection,

3500 lb Winch, Roof, Windshield, Aluminum Rims, Adjustable Gas Shocks, Lever Actuated Dump Bed

Camo, Dark Green

2 Year Limited

	ambient temperature, battery age, tire pressure, and installed accessories.
Chassis / Suspension / Brakes Suspension Front	Indep. Dual A-Arm / Nitrogen Assist
suspension Front	ilidep. Duai A-Amii / Nitrogeli Assist
Suspension Rear	Indep. Dual A-Arm / Nitrogen Assist
Brakes	4 Wheel Dual Ventilated Hydraulic Disc
Energy Recovery	Regenerative Braking
Tires Front	AT 26 x 9-14 Radial
Tires Rear	AT 26 x 11-14 Radial
Dimensions	
ength x Width x Height	110" × 61.75" × 73"
Wheel Base	72.5"
Vehicle Weight	1831 lbs.
Cargo Bed Capacity	500 lbs.
Towing Capacity	1500 lbs.
Ground Clearance	10"

Instrumentation / Special Features

Color Options

Warranty

Type	4-Stroke - OHV	4-Stroke - OHV
Displacement Bore & Stroke Compression Ratio Fuel System	Single Cylinder 735 cc 102 x 90 11 : 1 Delphi EFI	V-Twin Cylinders 976 cc 91 x 75 11 : 1 Delphi EFI
Cooling Ignition System	Liquid Electronic	Liquid Electronic
<b>Drive Train</b> Transmission	Automatic CVT	Automatic CVTech Trailbloc IBC
Drive System	4WD with Locking Front / Rear Differential	4WD with Locking Front / Rear Differential
Final Drive	L H N R Shaft Drive	L H N R Shaft Drive
Chassis / Suspension / Brakes Suspension Front	Indep. Dual A-Arm / Nitrogen Assist	Indep. Dual A-Arm / Nitrogen Assist
Suspension Rear	Indep. Dual A-Arm / Nitrogen Assist	Indep. Dual A-Arm / Nitrogen Assist
Brakes Front	Dual Ventilated Hydraulic Disc	Dual Ventilated Hydraulic Disc
Brakes Rear	Dual Ventilated Hydraulic Disc	Dual Ventilated Hydraulic Disc
Tires Front Tires Rear	AT 26 x 9-14 Radial AT 26 x 11-14 Radial	AT 27 x 9-14 Radial AT 27 x 11-14 Radial
Dimensions Length x Width x Height Wheel Base Fuel Capacity Vehicle Weight Cargo Bed Capacity Towing Capacity Ground Clearance	150" x 62" x 77" 109" 7.3 Gallons 1720 lbs. 350 lbs. 1200 lbs. 12"	155" x 65" x 78" 117" 7.3 Gallons 1881 lbs. 350 lbs. 1200 lbs. 13"
Other Instrumentation / Special Features	Digital-Analog Display, 3500 lb Winch, Roof, Windshield, Aluminum Rims, Adjustable Gas Shocks, Electronic Power Steering	Digital-Analog Display, Power Cargo Dump 4500 lb Winch, Roof, Windshield, Aluminum Rims, Adjustable Gas Shocks, Electronic Power Steering CVTech Trailbloc IBC Clutch
Compliance	EPA / CARB	EPA / CARB
Color Options	Camo, Black, Red	Camo, Black, Red
Warranty	2 Year Limited	2 Year Limited

### ALL TERRAIN VEHICLES

AXIS 110 FORGE 110 FORGE 250 FORGE 400









Engine				
Туре	Single Cylinder	Single Cylinder	1 Cylinder	1 Cylinder
Displacement	108 cc	108 cc	229 cc	393 cc
Bore & Stroke	52.4 x 50	52.4 × 50	65.5 x 68	84.5 x 70
Compression Ratio	9.5 : 1	9.5 : 1	9.7 : 1	9.3 : 1
Fuel System	Delphi EFI	Delphi EFI	Delphi EFI	Delphi EFI
Cooling	Air	Air	Liquid	Liquid
Ignition System	Electronic	Electronic	Electronic	Electronic
ig				
Drive Train				
Transmission	Automatic CVT	Automatic CVT	Automatic CVT	Automatic CVT
D: 0	OLAUD	2WD	OME	014/5 / 414/5
Drive System	2WD		2WD	2WD / 4WD
	FNR	FNR	FNR	FNR
Final Britis	Charles	Chair	Charles	Ch - G
Final Drive	Chain	Chain	Chain	Shaft
Chassis / Suspension / Brakes				
Suspension Front	Independent Dual A-arm	Independent Dual A-arm	Independent Dual A-arm	Independent Dual A-arm
	•	•	•	•
Suspension Rear	Swing Arm	Swing Arm	Swing Arm	Swing Arm
	, and the second	~	~	· ·
Brakes Front	Dual Ventilated Hydraulic Disc	Dual Ventilated Hydraulic Disc	Dual Ventilated Disc	Dual Ventilated Disc
Brakes Rear	Single Ventilated Hydraulic Disc	Single Ventilated Hydraulic Disc	Single Ventilated Disc	Single Ventilated Disc
	AT 21 x 7-8 Radial	AT 21 x 7-8 Radial	AT 25 x 8-12 Radial	AT 25 x 8-12 Radial
F				
Tires Front	AT 21 x 9.5-8 Radial	AT 21 x 9.5-8 Radial	AT 25 x 10-12 Radial	AT 25 x 10-12 Radial
Tires Rear				
Dimensions	645" 400" 406"	00.00 40.00 40.00	00.5" 40" 46"	00.5% 40% 46%
Length x Width x Height	64.5" x 40.9" x 40.6"	66.2" x 40.9" x 40.6"	82.5" x 42" x 46"	82.5" x 42" x 46"
Wheel Base	44"	44"	51.5"	51.5"
Fuel Capacity	1.84 Gallons	1.84 Gallons	2.6 Gallons	2.6 Gallons
Vehicle Weight	326 lbs.	361 lbs.	573 lb.	673 lb.
Cargo Rack Capacity	N/A	22 lb. Front / 33 lb. Rear	44 lb. Front / 77 lb. Rear	44 lb. Front / 77 lb. Rear
Towing Capacity	N/A	N/A	N/A	N/A
Ground Clearance	4.76"	4.76"	8"	8"
Other				
Instrumentation / Special Features	Analog Display, LED Lighting	Analog Display, LED Lighting,	Digital Display, LED Lighting,	Digital Display, LED Lighting,
motiamentation, opecial reatures	/ tidlog bisplay, EED Eighting	Front and Rear Cargo Racks	Front and Rear Cargo Racks,	Front and Rear Cargo Racks,
		FIGHT and Rear Cargo Racks		
			2500 lb Winch	2500 lb Winch
Compliance	EPA / CARB	EPA / CARB	EPA / CARB	EPA / CARB
Color Options	Blue, Red. Yellow	Camo, Dark Green, Red	Black, Camo, Red	Camo, Dark Green, Red
	Blac, Rea, Tellow	Carro, Dark Green, Rea	Bidek, Garrio, Red	camo, bark oreen, ked
Warranty	2 Year Limited	2 Year Limited	2 Year Limited	2 Year Limited
•				

17

# ALL TERRAIN VEHICLES

TACTIC 450 TACTIC 550 TACTIC 750 TACTIC 1000



2 Year Limited





2 Year Limited



2 Year Limited

Engine Engine				
Гуре	4-Stroke OHV	4-Stroke OHV	4-Stroke OHV	4-Stroke OHV
	Single Cylinder	Single Cylinder	Single Cylinder	V-Twin Cylinders
Pisplacement	454cc	546cc	735 cc	976 cc
ore & Stroke	83 x 84	52.4 x 50	84.5 x 70	91 x 75
Compression Ratio	9.4 : 1	9.6 : 1	9.7 : 1	11 : 1
sompression radio			30.11	
uel System	Delphi EFI	Delphi EFI	Delphi EFI	Delphi EFI
Cooling	Liquid	Liquid	Liquid	Liquid
gnition System	Electronic	Electronic	Electronic	Electronic
5, 111011 0, 010111	2.550.51115	2,000,01110	2.000.01110	210001011110
rive Train				
ransmission	Automatic CVT	Automatic CVT	Automatic CVT	Automatic CVTech Trailbloc IBC
Notice Constant	AMD with I salvis a Differential	AND with Lasting Differential	AVA/Dible I ==Itie = Diff==bi-1	AVA/Ditle I Line - Differential
Drive System	4WD with Locking Differential			
	LHNR	LHNR	LHNR	LHNR
Final Drive	Shaft	Shaft	Shaft	Shaft
Illai Drive	Shart	Silait	Shart	Silait
Chassis / Suspension / Brakes				
Suspension Front	Indep. Dual A-Arm / Nitrogen Assist			
suspension Rear	Indep. Dual A-Arm / Nitrogen Assist			
Brakes Front	Dual Ventilated Hydraulic Disc			
Brakes Rear	Single Ventilated Hydraulic Disc	Single Ventilated Hydraulic Disc	Single Ventilated Hydraulic Disc	Dual Ventilated Hydraulic Disc
Γires Front	AT 26 x 9-10 Radial	AT 26 x 9-10 Radial	AT 26 x 9-10 Radial	AT 27 x 9-14 Radial
ires Rear	AT 26 x 11-12 Radial	AT 26 x 11-12 Radial	AT 26 x 11-12 Radial	AT 27 x 11-14 Radial
imensions	00.7" 50.7" 54.7"	00.71 50.71 54.71	00.71	100" 510" 40"
ength x Width x Height	92.3" × 50.3" × 54.3"	92.3" × 50.3" × 54.3"	92.3" x 50.3" x 54.3"	100" x 51.6" x 49"
Vheel Base	57.2"	57.2"	57.2"	61.7"
uel Capacity	3.4 Gallons	3.4 Gallons	3.4 Gallons	5.2 Gallons
ehicle Weight	798 lbs.	853 lbs.	853 lb.	900 lb.
Cargo Rack Capacity	44 lb. Front / 77 lb. Rear			
owing Capacity	1200 lbs	1200 lbs	1200 lbs	1200 lbs
iround Clearance	11.61"	11.61"	11.61"	11"
Other				
nstrumentation / Special Features	Analog Display, LED Lighting,	Analog Display, LED Lighting,	Digital Display, LED Lighting,	Digital Display, LED Lighting,
	Front and Rear Cargo Racks,			
	2500 lb Winch	2500 lb Winch	2500 lb Winch	Electronic Power Steering
	2500 ID WITICIT	2500 ID WILLOIT	2500 ID WILLOTT	3500 lb Winch
				3500 ID WITICIT
Compliance	EPA / CARB	EPA / CARB	EPA / CARB	EPA / CARB
Color Options	Camo, Dark Green, Red			

2 Year Limited



Warranty



© HISUN 2017 All rights reserved. Version: 12081601